

## **Climbing Frame P4s**





Users (3 - 12 years): Required surface: 98 m<sup>2</sup> Assembly time by 2 pers.: 17 h


Shock-absorbing properties of playground area surface should comply with EN-1176 (e.g. rubber, mulch, sand, grass, gravel rated for a fall height ≥ 1.5 m)



Hy-Slide Green / Hy-Slide Steel







## The cut to size woodkit is manufactured from PEFC certified North-European spruce timber and high pressure impregnated.

Cross sections in woodkit: Posts: 110 x 110 mm

Joists: 44 x 68 mm Boards: 19 x 144 mm

Rebated boards: 19 x 145 mm

1x P - Kit A 2x P - Kit B 1x P - Kit C Kits:

> $1 \times S$  - Swing Module Start  $1 \times S$  - Swing Seats (2 pcs)

Hy-Slide: Timber package:

Item number: 171500402 EAN: 8711546156923

Packaging dimensions (W x D x H): 400 x 120 x 83 cm

Weight: 921 kg

Optional for non-paved construction site Number of Anchor Sets Uni (2 pcs): 5 sets

Concrete: 410 liter (≈820 kg)

For paved construction sites additional anchoring hardware is required: e.g. chemical anchors, expanding plugs/bolts

> Hy-land B.V. P.O. Box 75083 NL 1070 AB Amsterdam The Netherlands info@hy-land.eu