




Users (3 - 12 years): 8  
 Required surface: 88 m<sup>2</sup>  
 Assembly time by 2 pers.: 15 h

Shock-absorbing properties of playground area surface should comply with EN-1176 (e.g. rubber, mulch, sand, grass, gravel rated for a fall height  $\geq 1.5$  m)



Hy-Slide Green / Hy-Slide Steel



 **540 x 770 x 400 cm**

**The cut to size woodkit is manufactured from PEFC certified North-European spruce timber and high pressure impregnated.**

Cross sections in woodkit :

Posts : 110 x 110 mm

Joists : 44 x 68 mm

Boards : 19 x 144 mm

Rebated boards : 19 x 145 mm

Kits: 2x P - Kit A 1x P - Kit B 1x P - Kit C  
1 x S - Swing Module Start  
1 x S - Swing Seats (2 pcs)

Hy-Slide: 1

Timber package: 1

Item number: 171500502

EAN: 8711546156930

Packaging dimensions (W x D x H): 400 x 120 x 85 cm

Weight: 861 kg

Optional for non-paved construction site

Number of Anchor Sets Uni (2 pcs): 5 sets

Concrete: 410 liter (≈820 kg)

For paved construction sites additional anchoring hardware is required: e.g. chemical anchors, expanding plugs/bolts

Hy-land B.V.  
P.O. Box 75083  
NL 1070 AB Amsterdam  
The Netherlands  
info@hy-land.eu